

Notified body No.1121
Warrington Certification Limited, Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK

Certificate of Constancy of Performance

1121-CPR-KA5012

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Decorative Lincrusta Wallcoverings having a total weight of between 1429g/m² and 2387g/m².

Intended use: **Decorative Wall Covering**

Product Performance

| Harmonized Technical Specification - EN 15102:2007 + A1:2011 | | | |
|--|-------------|---|-----------------------------------|
| Essential Characteristics | Performance | Method | Report Reference |
| Reaction to fire | B-s2, d0 | EN 13501-1 | WF 350029 Exova Warringtonfire |
| Release of formaldehyde | Pass | Manufacturers declaration | N/A |
| Heavy Metals | Pass | Manufacturers declaration | N/A |
| Vinyl Monomer | Pass | Manufacturers declaration | N/A |
| Sound Absorption | NPD | EN ISO 354 (testing) EN ISO 11654 (classification) | Not Applicable |
| Thermal resistance | NPD | EN 12667 EN 12524 | Not Applicable |

Product Specification (See Page 3)

Certificate of Constancy of Performance

1121-CPR-KA5012

Produced for

HERITAGE WALLCOVERINGS LTD (LINCRUSTA PLANT)
Southgate
White Lund Industrial Estate
Morecambe
LA3 3PB

and produced in the manufacturing plant(s)

E/097

This is coded format and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

EN 15102:2007 + A1:2011

under system 1 of AVCP are applied and that

the product fulfils all the prescribed requirements set out above.

This certificate was first issued on **16/04/15** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.



Paul Duggan
Certification Manager
Warrington Certification Ltd

Certificate of Constancy of Performance

1121-CPR-KA5012

Product Specification

| | | | |
|--|--|--|---------------------------------|
| General description | | Lincrusta wallcovering | |
| Wall covering | Product reference of wall covering | Lincrusta Wallcovering | |
| | Name of manufacturer of wall covering | Heritage wallcoverings Ltd | |
| | Thickness of wall covering | 3000 to 4000 microns | |
| | Density / weight per unit area wall covering | 1429 to 2387g/m ² | |
| | Component 1 (test face) | Generic type | Vegetable oil based formulation |
| | | Product reference | Lincrusta putty |
| | | Detailed description / composition details | See note 1 below |
| | | Name of manufacturer | Heritage wallcoverings Ltd |
| | | Thickness | 2721 to 3721 microns |
| | | Weight per unit area | 1275 to 2233g/m ² |
| | | Colour reference | Natural/cream |
| | Backing / Scrim reinforcement (if applicable) | Flame retardant details | See note 1 below |
| | | Generic type | Paper |
| | | Product reference | See note 1 below |
| | | Name of manufacturer | See note 1 below |
| | | Thickness | 279 microns |
| | | Density / weight per unit area | 154 g/m ² |
| | | Type of weave / cell dimensions | A multi-layer construction |
| Adhesive | Flame retardant details | See note 2 below | |
| | Generic type | Acrylic based ready mixed adhesive | |
| | Product reference | "RDADH10" & "RDADH50" | |
| | Name of manufacturer | AFS Morecambe Ltd | |
| | Colour reference | "Off White" | |
| | Application rate / thickness | 0.2 l/m ² | |
| | Application method | Brush / roller | |
| | Flame retardant details | See Note 2 below | |
| Substrate | Curing process | Natural oxidation/absorption | |
| | Product reference | "NT D4 604" | |
| | Generic type | Fibre cement board | |
| | Name of manufacturer | Scheerders van de Kerkhove (SVK) | |
| | Thickness | 8mm | |
| Brief description of manufacturing process | Density | 1800kg/m ³ | |
| | Lincrusta is produced from a putty-like composition which is pre-mixed and applied to a heavy duty backing paper. The mixture is then embossed to form a deep pattern relief, following maturing proves an extremely tough and durable wallcovering. | | |

Note 1 - The sponsor of the test has provided this information but at the specific request of the sponsor, these details have been omitted from the report and are instead held on the confidential file relating to this investigation.

Note 2 – The sponsor stated that no flame retardant additives were utilised in the construction of the component.

----- End of Certificate -----